






These metallic glands are liquid tight, offer excellent strain relief and have lameller designed plastic inserts for protection against distortion. These glands are suitable for use in machinery and equipment, measuring and controlling devices, medical equipments and many other fields where exceptional stability and safe functioning is required. Cable glands with long thread length or reduced clamping range are also available on request.

STANDARD BRASS CABLE GLANDS




Technical Details :	
Material	Brass, Nickel Plated
Clamping Insert	Polyamide 6
Protection Class	IP 68
Sealing Ring	Neoprene
O Ring	Perbunan (NBR) / Silicone
Temperature Range	-40 ^o C to +100 ^o C
Threads available	Pg, Metric & NPT
Approvals	 


Pg Thread

Size	Cat. No.	Thread Diameter (mm)	Thread Length (mm)	 (mm)	Clamping Range (mm)	Standard Pack (pieces)
Pg 7	BSBC-01	13	6	14	3 - 6.5	50
Pg 9	BSBC-02	16	6	17	4 - 8	50
Pg 11	BSBC-03	19	6	20	5 - 10	50
Pg 13.5	BSBC-04	21	6.5	22	6 - 12	50
Pg 16	BSBC-05	23	6.5	24	10 - 14	25
Pg 21	BSBC-06	29	7	30	13 - 18	25
Pg 29	BSBC-07	37	8	40	18 - 25	20
Pg 36	BSBC-08	47	10	50	22 - 32	15
Pg 42	BSBC-09	54	12	58	30 - 38	12
Pg 48	BSBC-10	59	14	64	34 - 44	12

Metric Thread

Size	Cat. No.	Thread Diameter (mm)	Thread Length (mm)	 (mm)	Clamping Range (mm)	Standard Pack (pieces)
M 12 x 1.5	BMBC-0S	12	6	14	3 - 6.5	50
M 16 x 1.5	BMBC-01	16	7	17	4 - 8	50
M 16 x 1.5	BMBC-E1	16	7	20	5 - 10	50
M 20 x 1.5	BMBC-02	20	8	22	6 - 12	20
M 25 x 1.5	BMBC-03	25	8	24	10 - 14	20
M 25 x 1.5	BMBC-E3	25	8	27	11 - 17	20
M 32 x 1.5	BMBC-04	32	9	30	13 - 18	10
M 32 x 1.5	BMBC-E4	32	8	34	15 - 21	10
M 40 x 1.5	BMBC-05	40	9	40	18 - 25	10
M 40 x 1.5	BMBC-E5	40	9	43	19 - 28	10
M 50 x 1.5	BMBC-06	50	9	50	22 - 32	5
M 63 x 1.5	BMBC-07	63	14	64	34 - 44	5
M 63 x 1.5	BDSM-07	63	16	77	50 - 56	5
M 72 x 2	BDSM-08	72	16	77	56 - 61	5
M 75 x 2	BDSM-09	75	16	77	56 - 61	5
M 80 x 2	BDSM-10	80	18	90	60 - 66	2
M 85 x 2	BDSM-11	85	22	96	68 - 76	2
M 90 x 2	BDSM-12	90	22	98	68 - 76	2

NPT Thread

Size	Cat. No.	Thread Diameter (mm)	Thread Length (mm)	 (mm)	Clamping Range (mm)	Standard Pack (pieces)
NPT 3/8"	BNBC-01	16	15	17	4 - 8	50
NPT 1/2"	BNBC-02	21	13	22	6 - 12	50
NPT 3/4"	BNBC-03	29	13	30	13 - 18	20
NPT 1"	BNBC-04	33.2	13	43	18 - 25	20