



CONNECTORS TO SECURE

CABLES AND CONDUITS



These special connectors are used to clamp flexible corrugated conduits. They offer IP67 protection and are available in Pg and UNEF threads. These connectors also act as a cable gland for the cable going through the conduit.

Technical Details :	
Material	Polyamide 6
Colour	RAL 7001 (Grey) RAL 9005 (Black)
Temperature Range	-40° C to +105° C Continuous, +150° C Short Term
Protection Class	IP 67
Threads available	Pg & Metric - Male Thread* , UNEF - Female Thread

### Pg Male Thread

Size	Suitable for Conduit Size	Cat. No. Grey	Cat. No. Black	Thread Length (mm)	Clamping Range (mm)	Standard Pack (pieces)
Pg 7	10	TNCC-P07G	TNCC-P07B	13	3.5 - 6.5	50
Pg 9	10	TNCC-P09G	TNCC-P09B	13	3.5 - 6.5	50
Pg 11	12	TNCC-P11G	TNCC-P11B	15	4 - 8	30
Pg 13.5	16	TNCC-P13G	TNCC-P13B	15	8 - 12	30
Pg 16	16	TNCC-P16G	TNCC-P16B	15	8 - 12	30
Pg 21	22	TNCC-P21G	TNCC-P21B	15	12 - 16	30
Pg 29	28	TNCC-P29G	TNCC-P29B	15	20 - 24	15
Pg 36	36	TNCC-P36G	TNCC-P36B	19	28 - 32	15
Pg 48	48	TNCC-P48G	TNCC-P48B	19	32 - 38	10

\* Metric Male Thread Connectors available on request.

### UNEF Female Thread

UNEF Thread Size	Suitable for Conduit Size	Cat. No. Grey	Cat. No. Black	Inner Thread Length (mm)	Cable Clamping Range (mm)	Standard Pack (pieces)
1/2-28	10	TICC-U1010G	TICC-U1010B	13	3.5-6.5	50
5/8-24	10	TICC-U1210G	TICC-U1210B	13	3.5-6.5	30
3/4-20	10	TICC-U1410G	TICC-U1410B	13	3.5-6.5	30
5/8-24	12	TICC-U1212G	TICC-U1212B	13	4-8	30
3/4-20	12	TICC-U1412G	TICC-U1412B	13	4-8	30
1-20	12	TICC-U1812G	TICC-U1812B	13	4-8	30
7/8-20	16	TICC-U1616G	TICC-U1616B	13	7-12	30
1-20	16	TICC-U1816G	TICC-U1816B	13	7-12	30
1 3/16-18	16	TICC-U2016G	TICC-U2016B	13	7-12	30
1 7/16-18	16	TICC-U2816G	TICC-U2816B	15	7-12	30
1 3/16-18	22	TICC-U2222G	TICC-U2222B	15	12-16	30
1 7/16-18	22	TICC-U2822G	TICC-U2822B	15	12-16	30
1 7/16-18	28	TICC-U2828G	TICC-U2828B	15	18-26	20
1 3/4-18	28	TICC-U3228G	TICC-U3228B	15	18-26	10
2-18	28	TICC-U3628G	TICC-U3628B	15	18-26	10
2-18	36	TICC-U3636G	TICC-U3636B	19	22-33	10