






EXPLOSION PROOF Ex-E

POLYAMIDE CABLE GLAND



These Glands are for use with electrical equipment in potentially explosive areas, specially in chemical and petro-chemical industries. These Glands are produced accordance to Directive 94/9/EC, EN 60079-7:2007.

Technical Details :	
Material	Polyamide 6
Colour	RAL 9005 (Black)
Protection Class	IP 68, 5 bar
Sealing Ring	Neoprene
Dust Guard	Assembled
Temperature Range	-20°C to +80°C
Conformity Number	IMQ 08 ATEX 012X
Type of Protection	Ex e II, Ex-i
Threads available	Metric
Approvals	CE  I I 2GD 

Size	Cat. No. Black	Thread Diameter (mm)	Thread Length (mm)	 (mm)	Clamping Range (mm)	Standard Pack (pieces)
M 12 x 1.5	BM-XS	12	8	15	4 - 7	100
M 16 x 1.5	BM-X1	16	10	22	5.5 - 10	50
M 20 x 1.5	BM-X2	20	10	24	5.5 - 13	50
M 25 x 1.5	BM-X5	25	10	33	8 - 17.5	25
M 32 x 1.5	BM-X7	32	18	42	12 - 21	20
M 40 x 1.5	BM-X8	40	18	53	17 - 28	10
M 50 x 1.5	BM-X9	50	18	60	22 - 35	10
M 63 x 1.5	BM-X0	63	18	65	27 - 48	10