



These connectors are used to clamp flexible corrugated conduits. They offer IP67 protection and are available in special UNEF and PF thread configuration.

Technical Details :	
Material	Polyamide 6
Colour	Black & Grey
Temperature Range	-40°C to +105°C Continuous, +150°C Short Term
Protection Class	IP 67
Threads available	UNEF, PF

STRAIGHT CONNECTORS

WITH FEMALE THREADS



### UNEF Thread

UNEF Thread Size	Suitable for Conduit Size	Cat. No. Grey	Cat. No. Black	Inner Thread Length (mm)	Standard Pack (pieces)
1/2-28	10	TIC-U1010G	TIC-U1010B	14	50
5/8-24	10	TIC-U1210G	TIC-U1210B	14	50
3/4-20	10	TIC-U1410G	TIC-U1410B	14	50
5/8-24	12	TIC-U1212G	TIC-U1212B	14	50
3/4-20	12	TIC-U1412G	TIC-U1412B	14	50
1-20	12	TIC-U1812G	TIC-U1812B	14	50
7/8-20	16	TIC-U1616G	TIC-U1616B	14	50
1-20	16	TIC-U1816G	TIC-U1816B	14	30
1 3/16-18	16	TIC-U2016G	TIC-U2016B	14	30
1 7/16-18	16	TIC-U2816G	TIC-U2816B	14	30
1 3/16-18	22	TIC-U2222G	TIC-U2222B	15	30
1 7/16-18	22	TIC-U2822G	TIC-U2822B	15	30
2-18	22	TIC-U3622G	TIC-U3622B	15	30
1 7/16-18	28	TIC-U2828G	TIC-U2828B	15	30
1 3/4-18	28	TIC-U3228G	TIC-U3228B	15	30
2-18	28	TIC-U3628G	TIC-U3628B	15	30
2-18	36	TIC-U3636G	TIC-U3636B	15	30

### PF Thread

PF Thread Size	Suitable for Conduit Size	Cat. No. Grey	Cat. No. Black	Inner Thread Length (mm)	Standard Pack (pieces)
G 1/2"	16	TIPC-G16G	TIPC-G16B	13.8	50
G 3/4"	22	TIPC-G22G	TIPC-G22B	15	30
G 1"	28	TIPC-G28G	TIPC-G28B	15	25
G 1 1/4"	36	TIPC-G36G	TIPC-G36B	29	10
G 1 1/2"	48	TIPC-G42G	TIPC-G42B	29	10
G 2"	48	TIPC-G48G	TIPC-G48B	29	10

### PG Thread

PG Thread Size	Suitable for Conduit Size	Cat. No. Grey	Cat. No. Black	Inner Thread Length (mm)	Standard Pack (pieces)
Pg 11	12	TIC-P11G	TIC-P11B	14	50
Pg 13.5	12	TIC-P132G	TIC-P132B	14	50
Pg 16	16	TIC-P16G	TIC-P16B	14	30
Pg 21	22	TIC-P21G	TIC-P21B	15	30

### Metric Thread

Metric Thread Size	Suitable for Conduit Size	Cat. No. Grey	Cat. No. Black	Inner Thread Length (mm)	Standard Pack (pieces)
M16 x 1.5	12	TIC-M12G	TIC-M12B	14	50
M16 x 1.5	16	TIC-M226G	TIC-M226B	14	50